

رقيط للغازات الصـناعـية Rakeeth Industrial Gases

MATERIAL SAFETY DATA SHEET (MSDS) MEDICAL CARBON DIOXIDE- CO2

1 PRODUCT AND COMPANY IDENTIFICATION PRODUCT IDENTIFICATION

Product Name Chemical Formula Company Identification

CARBON DIOXIDE CO_2 RAKEETH IND GASES CO LLC 483/1 Street Al Sajaa industrial area Sharjah, UAE Mob. No: 0565264603 Tel No: 06526161

EMERGENCY No. 997 CIVIL DEFENCE UAE

2 COMPOSITION/INFORMATION ON INGREDIENTS

Trade Names	R744
Chemical Name	Carbon Dioxide
Chemical Family	Carbon Anhydride
Synonyms	Carbonic Acid Gas
CAS No.	124-38-9
UN No.	1013
Hazchem Code:	2 XE
Hazchem Warning	2 C Non flammable gas

3 HAZARDS IDENTIFICATION

Main Hazards	Carbon dioxide does not support life. It can act
	as a simple asphysiant by diluting the
	concentration of oxygen in air below the levels
	necessary to support life. As it is heavier than
	air it will tend to concentrate at lower levels.
Adverse Health	Carbon dioxide acts as a stimulant and a
Effects	depressant on the central nervous system.
	Increases in heart rate and blood pressure have
	been noted at a concentration of 7.6 percent,
	and dyspnea (laboured breathing), headache,
	dizziness and sweating occur if exposure at that
	level is prolonged.
Chemical Hazards	Carbon dioxide is relatively non-reactive and
	non-toxic. On the presence of moisture it can
	aggressively bring about corrosion in a variety
	of steel materials
Biological Hazards	The greatest physiological effect of carbon
100	dioxide is to stimulate the respiratory centre,
	thereby controlling the volume and rate of
	respiration. It is able to cause dilation and
	constriction of blood vessels and is a vital
	constituent of the acid-base mechanism that
-	controls the pH of the blood.
Vapour Inhalation	At concentrations of 10% and above,
•	unconsciousness can result in one minute or
	less. Impairment in performance has been
	notedduringprolongedexposureto
	concentrations of 3% carbon dioxide even
1	when the oxygen concentration was 21%
Eve Contact	No known effect
Skin Contact	No known effect
Ingestion	(See "Vapour Inhalation")
Ingestion	(See "Vapour Inhalation")

4 FIRST AID MEASURES

Prompt medical attention is mandatory in all cases of overexposure to carbon dioxide. Rescue personnel should be equipped with selfcontained breathing apparatus. Gaseous carbon dioxide is an asphyxiant. Concentrations of 10% or more can produce unconsciousness or death. Lower concentrations may cause headache, sweating, rapid breathing, increased heartbeat, shortness of

breath, dizziness, mental depression, visual disturbances and shaking. Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be removed to an uncontaminated area, and given mouth-to-mouth resuscitation and supplemental oxygen. **Eye Contact** No known effect. **Skin Contact** No known effect. Ingestion (See Section 3 above). **5 FIRE FIGHTING MEASURES** Extinguishing media Carbon dioxide is an extinguishing medium. Specific Hazards Carbon dioxide does not support life. It can act as a simple asphyxiant by diluting the concentration of oxygen in the air below the levels to support life. **Emergency Actions** If possible, shut off the source of excess carbon dioxide. Evacuate area. All cylinders should be removed should be removed from the vicinity of the fire. Cylinders that cannot be removed should be cooled with water from a safe distance. Cylinders which have been exposed to excessive heat should be clearly identified and returned to the supplier. Self-contained breathing apparatus. **Protective Clothing** Safety gloves and shoes or boots should be worn when handling cylinders. Environmental Carbon dioxide is heavier than air and could Precautions accumulate in low-lying areas. Care should be taken when entering a potentially oxygen deficient environment. If possible, ventilate the affected area. 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions	Do not enter any area where carbon dioxide	
1	has been spilled unless tests have shown that	
	it is safe to do so.	
Environmental	As carbon dioxide is classified as a "green	
Precautions	house" gas, any spillage should be avoided at all times.	
Small spills	shut off the source of escaping carbon dioxide. Ventilate the area.	
Large spills	Evacuate the area. Shut off the source of the spill if this can be done without risk. Restrict	
	access to the area until completion of the clean-up procedure. Ventilate the area using	
	forced-draft if necessary.	

HANDLING AND STORAGE

Do not allow cylinders to slide or come into contact with sharp edges. Carbon dioxide cylinders should be stacked vertically at all times, and should be firmly secured in order to prevent them from being knocked over. Use a "first-in first-out" inventory system to prevent full cylinders from being stored for excessive periods of time. Keep out of reach of children. API 10

- 10 III III III III III I	- 100 ALC - 107 - 100 ALC - 1	
8 EXPOSURE CO	NTROLS/PERSONAL PROTECTION	
Occupational	As carbon dioxide is a simple asphyxiant,	
Exposure	avoid any areas where spillage has taken place.	
Hazards	Only enter once testing has proved the	
	atmosphere to be safe, and remember that the	
gas is heavier than air.		
Engineering control	Engineering control measures are preferred to	



رقيط للغازات الصـناعـية Rakeeth Industrial Gases

Measures	reduce exposure to oxygen-depleted atmospheres. General methods include forced-draft ventilation, separate from other exhaust ventilation systems.Ensure that sufficient fresh air enters at, or near, floor level.
Personal protection Skin	Self-contained breathing apparatus should always be worn when entering area where oxygen depletion may have occurred. Safety goggles, gloves and shoes or boots should be worn when handling cylinders. No known effect.

9 PHYSICAL AND CHEMICAL PROPERTIES

PYSICAL DATA	
Chemical Symbol	CO ₂
Molecular Weight	44,011
Specific volume @ 20°C & 101,325 kPa	547 ml/g -
Sublimation point @ 101,325 kPa	78,45°C -
Triple point temperature	56,6°C
Triple point pressure	517,.97 kPa
* * *	1,839 kg/m ³
Density, liquid @ boiling point	156,0 kg/m ³
Density gas @ 101,325 kPa & 20°C	1,53
Relative density (Air=1) @ 101,325 kPa	31,0°C
Critical temperature	7382,5 kPa
Critical pressure	2,137 ml/g
Critical volume	0,468 g/ml
Critical density	0,274
Critical compressibility factor	570.7 kJ/kg
Latent heat of vapourisation @ boiling point	None Acidic
Colour	None
Taste	1
Odour	

10 STABILITY AND REACTIVITY

Conditions to avoid	The dilution of oxygen in the atmosphere to
	levels which cannot support life. Never use
	cylinders as rollers or supports, or for any
	other purpose than the storing of carbon
	dioxide.Never expose the cylinders to
	excessive heat, as this may cause sufficient
	build-up of pressure to rupture the cylinders.
Incompatible	As dry carbon dioxide is inert it may be
materials	contained in systems constructed of any of
	the common metals which have been
	designed to safely withstand the pressures
	involved.
Hazardous	No known effect.
Decomposition produ	icts

11 TOXICOLOGICAL INFORMATION

	A CONTRACT OF A
Acute Toxicity	TLV 5000 VPM
Skin & eye contact	No known effect
Chronic Toxicity	No known effect
Carcinogenicity	No known effect
Mutagenicity	No known effect

Reproductive Hazards No known effect (For further information see Section 3. Adverse Health Effects).

12 ECOLOGICAL INFORMATION

Carbon dioxide is heavier than air and can cause pockets of oxygendepleted atmosphere in low-lying areas. It does not pose a hazard to the ecology.

13 DISPOSAL CONSIDERATIONS

Disposal Methods	Small amounts may be blown to the atmosphere under controlled conditions.
Disposal of packaging	Large amounts should only be handled by the gas supplier. The disposal of cylinders must only be handled by the gas supplier.

14 TRANSPORT INFORMATION DO AD TO ANGDODT ATION

RUAD TRANSPORTATION	
UN No.	1013
Hazchem code	2 XE
Hazchem warning	2C Non-flammable gas
SEA TRANSPORTATION	-
IMDG	1013
Class	
Packaging group	
Label	Non-flammable gas
AIR TRANSPORTATION	-
ICAO/IATA Code	1013
Class	2.2
Packaging group	
Packaging instructions	
- Cargo	200
- Passenger	200
Maximum quantity allowed	
- Cargo	150 kg
- Passenger	75 kg